

Features:

- ▶ Hand crafted in die-cast aluminium bronze.
- ▶ Rolled brass main body.
- ▶ 10 year non-corrosion guarantee.
- ▶ Resistant to shock, weather and vandals.
- ▶ Simple to install.
- ▶ Safe extra low voltage.
- ▶ Heat Dispersing.
- ▶ Anti-corrosive.
- ▶ Auto resetting, thermal safety cut out.
- ▶ Marine grade 316 stainless steel fixings.
- ▶ Optional anti-glare louvers.
- ▶ Optional patterned glass for light control.
- ▶ Up and down lighting.



Standard specifications:

Order code	RL880
Overall size	55 mm(DIA) x 240mm(H) x 120(W)
Mounting	Wall.
Body material	Die-cast aluminium bronze and rolled brass body.
Fixings	Assembled with marine grade 316 stainless steel fittings.
Glass	Clear 5mm neoceramic glass.
Lamp type	MR16 12 volt tungsten halogen.
Lamp wattage	2 x 20 watt / 38° (total 40 watts)
Power entry	Base entry.
Protection	120°c auto resetting thermal switch.

Options: (ORDER CODE)

Glass	Frosted neoceramic glass (RFL)
Anti-glare	Anti-glare louver (RLSL51)
Spreader lenses	Skytex (RLSL5101) Solite (RLS5102) Crystal (RL5103) Flashed opal (RLSL5101)

CAUTION: Fittings can become very hot. 20 watts maximum recommended where fittings can be touched while operating.

