

## Features:

- ▶ Hand crafted in die-cast aluminium bronze.
- ▶ Rolled brass main body.
- ▶ 10 year non-corrosion guarantee.
- ▶ Resistant to shock, weather and vandals.
- ▶ Simple to install.
- ▶ Safe extra low voltage.
- ▶ Heat Dispersing.
- ▶ Anti-corrosive.
- ▶ Auto resetting, thermal safety cut out.
- ▶ Marine grade 316 stainless steel fixings.
- ▶ Optional anti-glare louvers.
- ▶ Optional patterned glass for light control.
- ▶ Directional lighting.



## Standard specifications:

Order code	<b>RL885</b>
Overall size	55 mm(DIA) x 215 mm(H)
Mounting	Wall.
Body material	Die-cast aluminium bronze and rolled brass body.
Fixings	Assembled with marine grade 316 stainless steel fittings.
Glass	Clear 5mm neoceramic glass.
Lamp type	MR16 12 volt tungsten halogen.
Lamp wattage	20 watt / 38°
Power entry	Base entry.
Protection	120°c auto resetting thermal switch.

## Options: (ORDER CODE)

Glass	Frosted neoceramic glass (RFL)
Anti-glare	Anti-glare louver (RLSL51)
Spreader lenses	Skytex (RLSL5101) Solite (RLS5102) Crystal (RL5103) Flashed opal (RLSL5101)

CAUTION: Fittings can become very hot. 20 watts maximum recommended where fittings can be touched while operating.

